

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau(43) International Publication Date
20 February 2003 (20.02.2003)

PCT

(10) International Publication Number
WO 03/013307 A1

- (51) International Patent Classification⁷: **A47B 23/04** (74) Agent: YERKESON, Douglas, A.; Bose McKinney & Evans LLP, 2700 First Indiana Plaza, 135 North Pennsylvania Street, Indianapolis, IN 46204 (US).
- (21) International Application Number: PCT/US02/24619
- (22) International Filing Date: 2 August 2002 (02.08.2002) (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZM, ZW.
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
60/310,092 3 August 2001 (03.08.2001) US
- (71) Applicant: HILL-ROM SERVICES, INC. [US/US]; 300 Delaware Avenue, Suite 530, Wilmington, DE 19801 (US).
- (72) Inventors: GEORGE, Christopher; 7863 Dimmick Road, Cincinnati, OH 45241 (US). ZERHUSEN, Robert, M.; 10186 Owl Creek Road, Cincinnati, OH 45252 (US). RILEY, Carl, W.; 3773 North State Road 129, Milan, IN 47031 (US). REEDER, Ryan, Anthony; 9901 Culpepper Avenue, Carmel, IN 46032 (US). CERIMELE, Michael, E.; 148 South Emerson Avenue, Indianapolis, IN 46219 (US). HORNBACH, David, W.; 12161 County Line Road, Brookville, IN 47012 (US). WALKER, Michelle, Larsen; 355 East Vista Ridge Mall Drive, #3225, Lewisville, TX 75067 (US).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

WO 03/013307 A1

(54) Title: OVERBED TABLE FOR USE WITH A PATIENT SUPPORT

(57) Abstract: An overbed table (10) configured to support a table section (16) above a patient support surface, such as a hospital bed (21). The overbed table (10) includes a frame (15) having a base (12) and a substantially vertical support column (14) for supporting the table section (16). In one illustrative embodiment, a display device (124) is supported by the overbed table (10). In a further illustrative embodiment, a camera (160) is supported by the overbed table (10).

BEST AVAILABLE COPY

WO 03/013307

PCT/US02/24619

-1-

OVERBED TABLE FOR USE WITH A PATIENT SUPPORT**Background and Summary of the Invention**

5 This invention relates generally to overbed tables of the type extending above a patient support surface. More particularly, the invention relates to an overbed table incorporating a display device and/or a camera configured to be used by a patient supported on a hospital bed or by a caregiver located adjacent to the bed.

The present invention provides an overbed table of the type cantilevered over a patient support, such as a hospital bed, and configured to support materials utilized
10 by a patient.

According to an illustrative embodiment of the invention, an overbed table includes a frame coupled to first and second table sections, wherein the second table section is supported in vertically spaced relation to the first table section. A support is positioned in vertical spaced relation to the first table section and is configured to
15 move relative to the first table section within a substantially horizontal plane. A display screen is coupled to the support and is configured to move between a substantially horizontal storage position and a substantially vertical use position.

Illustratively according to the embodiment, at least one of the first table section and the second table section is configured to move in a substantially
20 horizontal plane with respect to the other of the second table section and the first table section. Illustratively, the second table section is coupled to the first table section and the frame such that movement of the second table section results in sliding movement of the first table section.

Further illustratively according to the embodiment, the support comprises an
25 arm having first and second handles, wherein the display screen is supported intermediate the first and second handles.

Illustratively according to the embodiment, the support is pivotably connected to the first table section.

Illustratively according to the embodiment, the display screen is coupled to the
30 support for pivoting movement about a substantially horizontal first axis and for pivoting movement about a second axis extending substantially perpendicular to the first axis.

WO 03/013307

PCT/US02/24619

-2-

Further illustratively according to the embodiment, the display screen is located intermediate the first and second table sections in the storage position and extends above the first table section in the use position.

Illustratively according to the embodiment, the display screen comprises one of a flat panel monitor and a reflective mirror.

Illustratively according to the embodiment, a camera is supported proximate the display screen.

Further illustratively according to the embodiment, the first table section is supported by the frame for movement between a generally vertical position and a generally horizontal position.

Further illustratively according to the embodiment, the second table section is releasably coupled to the first table section and the frame permits movement of the first table section between a generally vertical position and a generally horizontal position independently of the second table section.

Illustratively according to the embodiment, the first table section is supported by the frame by an inner member provided on one of the frame and the first table section and an outer member provided on the other of the frame and the first table section, the inner member extending rotatably and slidably through the outer member to permit sliding movement and pivoting movement of the first table section with respect to the frame.

Further illustratively according to the embodiment, a rest is supported by one of the frame and the first table section, the rest configured to support the first table section in the generally horizontal position.

Illustratively according to the embodiment, the frame includes a telescoping support column having an outer column portion and an inner column portion, the telescoping support column supporting the first and second table sections, and a base coupled to the telescoping support column.

Further illustratively according to the embodiment, the second table section is coupled to the first table section by a first pivotal coupling between the first and second table sections.

Illustratively according to the embodiment, the first pivotal coupling includes a first bearing provided on one of the first and second table sections and a bearing race provided on the other of the first and second table sections, the first bearing

WO 03/013307

PCT/US02/24619

-3-

engaging the bearing race to permit pivoting of the second table section about a first axis with respect to the first table section. The second table section is illustratively coupled to the frame by a second pivotal coupling between the second table section and the frame.

5 Illustratively according to the embodiment, the second pivotal coupling includes a trunnion provided on one of the frame and the second table section and a recess provided on the other of the frame and the second table section for receiving the trunnion to permit pivoting of the second table section about a second axis with respect to the first table section, the second axis being spaced from the first axis.

10 Illustratively according to the embodiment, the display screen is coupled to the first table section by a third pivotal coupling connected to the first table section.

Further illustratively according to the embodiment, a processor is provided in communication with the display screen.

15 Illustratively according to the embodiment, a connector is supported by the frame and is configured to operably connect with a bed frame for placing the display screen in communication with a processor.

According to a further embodiment of the invention, an overbed table includes a frame having a vertically extending support column, a table section supported by the frame and configured to cantilever over a patient support surface including opposing
20 head and foot ends, and a camera supported by the frame and directed toward the head end of the patient support.

Illustratively according to the embodiment, a display screen is supported by the frame and includes a viewable surface directed toward the head end of the patient support surface. The camera is illustratively supported by the display screen.

25 Further illustratively according to the embodiment, a support is configured to move relative to the table section within a substantially horizontal plane, the display screen being coupled to the support and configured to move between a substantially horizontal storage position and a substantially vertical use position.

30 Illustratively according to the embodiment, a processor is supported by the frame and is in communication with the camera.

Further illustratively according to the embodiment, a connector is supported by the frame and is configured to operably connect with a bed frame for placing the camera in communication with a remote processor.

WO 03/013307

PCT/US02/24619

-4-

Illustratively according to the embodiment, at least one solar cell is supported by the frame and is operably connected to the camera, wherein the at least one solar cell is alignable with a light source connected to the patient support surface.

According to a further illustrative embodiment of the invention, an overbed
5 table includes a frame having a vertically extending support column, and a table section supported by the frame and configured to cantilever over a patient support surface including opposing head and foot ends, and a display device supported by the frame and coupled to a power source. The display device includes first and second sides, and a viewable surface supported by the first side and directed toward the head
10 end of the patient support.

Illustratively according to the embodiment, a camera is supported by the frame and is directed toward the head end of the patient support surface. The camera is provided in communication with the display device, thereby defining an electronic mirror.

15 Further illustratively according to the embodiment, the camera is supported by the display device.

Illustratively according to the embodiment, a support is configured to move relative to the table section within a substantially horizontal plane, the display device being coupled to the support and configured to move between a substantially
20 horizontal storage position and a substantially vertical use position.

Further illustratively according to the embodiment, a processor is supported by the frame and is in communication with the display device.

Illustratively according to the embodiment, a connector is supported by the frame and is configured to operably connect to a bed frame for placing the display
25 device in communication with a remote processor.

Further illustratively according to the embodiment, at least one solar cell is supported by the frame and is operably connected to the display device, wherein the at least one solar cell is alignable with a light source connected to the patient support surface.

30 Illustratively according to the embodiment, a reflective mirror is supported by the second side of the display device.

According to another illustrative embodiment of the invention, an overbed table includes a table section having upper and lower surfaces, the table section being

WO 03/013307

PCT/US02/24619

-5-

configured to cantilever over a patient support surface. The overbed table further includes a support positioned in vertical spaced relation to the table section, at least one of the table section and the support being configured to move relative to the other of the support and the table section, and a monitor coupled to the support and in
5 communication with a power source.

Illustratively according to the embodiment, the monitor is coupled to the support for movement between a storage position below the lower surface of the first table section and a use position extending above the upper surface of the first table section.

10 Illustratively according to the embodiment, the support comprises an arm pivotally supported below the lower surface of the table section for pivoting movement about a substantially vertical axis.

Further illustratively according to the embodiment, a coupler connects the monitor and the arm, the coupler supporting the monitor for a first pivoting movement
15 about a substantially horizontal axis and for a second pivoting movement about a second axis substantially perpendicular to the first axis.

Further illustratively according to the embodiment, a keyboard is coupled to the support.

Further illustratively according to the embodiment, the support comprises a
20 tray slidably supported below the table section and defining a storage compartment, the monitor being supported by the tray for pivoting movement about a substantially horizontal axis. The monitor is illustratively configured to fold into the storage compartment beneath the table section.

Illustratively according to the embodiment, the monitor is supported by an arm
25 configured to move vertically relative to the table section. The arm illustratively includes a vertical portion, a horizontal portion pivotally connected to the vertical portion, and a coupler connecting the monitor to the horizontal portion. The coupler supports the monitor for a first pivoting movement about a first axis and for a second pivoting movement about a second axis disposed substantially perpendicular to the
30 first axis.

According to yet another illustrative embodiment of the invention, an overbed table includes a frame, a housing coupled to the frame and defining a storage compartment, and a table section coupled to the housing. The table section is

WO 03/013307

PCT/US02/24619

-6-

supported for movement between first and second positions, the first position substantially covering the storage compartment and the second position providing access to the storage compartment. A display screen is coupled to a power source and is removably supported within the storage compartment.

5 Illustratively according to the embodiment, the display screen is supported by an arm including a vertical portion. The arm illustratively includes a horizontal portion coupled to the vertical portion, and a coupler connects the display screen to the horizontal portion. The coupler supports the display screen for a first pivoting movement about a first axis and for a second pivoting movement about a second axis
10 disposed substantially perpendicular to the first axis.

Illustratively according to the embodiment, a collapsible stand is coupled to the display screen for supporting the display screen on an upper surface of the table section.

Further illustratively according to the embodiment, the display screen
15 comprises a flat panel monitor.

Illustratively according to the embodiment, a processor is in communication with the display screen.

Further illustratively according to the embodiment, a connector is supported by the frame and is configured to operably connect with a bed frame for placing the
20 display screen in communication with a remote processor.

Additional features of the invention will become apparent to those skilled in the art upon consideration of the following detailed description when taken in conjunction with the accompanying drawings.

25 Brief Description of the Drawings

The detailed description particularly refers to the accompanying figures in which:

Fig. 1 is a perspective view of an illustrative embodiment overbed table of the present invention, illustrating the second table section and the display support in
30 closed or storage positions;

Fig. 2 is a perspective view similar to Fig. 1, illustrating the second table section and the display support in open or use positions;

Fig. 3 is a partially exploded perspective view of the overbed table of Fig. 1;

WO 03/013307

PCT/US02/24619

-7-

Fig. 4 is a top plan view, with a partial cut-away, of the overbed table of Fig. 1;

Fig. 5 is a top plan view similar to Fig. 4, illustrating the second table section in an open or use position and the display support in a closed or storage position;

5 Fig. 6 is a top plan view similar to Fig. 4, illustrating the second table section and the display support in open or use positions;

Fig. 7 is a perspective view of the overbed table of Fig. 1 illustrating the first table section in an upright or cleaning position;

10 Fig. 8 is a detailed perspective view of the overbed table, with a partial cut-away of the display coupler;

Fig. 9 is a perspective view of a further illustrative embodiment overbed table of the present invention, illustrating the second table section and the display screen in open positions;

15 Fig. 10 is a perspective view similar to Fig. 9, illustrating the second table section in a closed position;

Fig. 11 is a perspective view of yet another illustrative embodiment overbed table of the present invention, illustrating the first table section and the display screen in open positions;

20 Fig. 12 is a perspective view similar to Fig. 11, illustrating the first table section in a closed position;

Fig. 13 is a perspective view of a further illustrative embodiment overbed table of the present invention, illustrating the display screen in a fully deployed or use mode of operation;

25 Fig. 14 is a perspective view similar to Fig. 13, illustrating the display screen in a stored mode of operation;

Fig. 15 is a perspective view of the overbed table of Fig. 13, illustrating the display screen in a first partially deployed mode of operation;

Fig. 16 is a perspective view of the overbed table of Fig. 13, illustrating the display screen in a second partially deployed mode of operation;

30 Fig. 17 is a perspective view of a further illustrative embodiment overbed table of the present invention, illustrating the display screen incorporated within a phone and positioned in a fully deployed or use mode of operation;

WO 03/013307

PCT/US02/24619

-8-

Fig. 18 is a perspective view similar to Fig. 17, illustrating the display screen in a stored mode of operation;

Fig. 19 is a perspective view of a further illustrative embodiment overbed table of the present invention, illustrating a display screen pivotally supported in a storage position within a storage compartment and positioned in a use mode of operation extending above the first table section;

Fig. 20 is a perspective view similar to Fig. 19, illustrating the display screen in a storage position below the first table section;

Fig. 21 is a front perspective view of a further illustrative embodiment overbed table of the present invention, illustrating a display screen configured to be removably supported within a storage compartment below the table section in a storage position and supported on the table section in a use position;

Fig. 22 is a perspective view of the display screen similar to that of Fig. 21 with the display screen rotated 180° about a vertical axis;

Fig. 23 is a perspective view of a further illustrative embodiment overbed table of the present invention, illustrating a docking connector and a solar power device supported by the base of the frame of the overbed table; and

Fig. 24 is a cross-sectional view illustrating the interaction of the overbed table of Fig. 23 when fully docked to a hospital bed.

Detailed Description of the Drawings

Referring initially to Figs. 1-3, an overbed table 10 according to an illustrative embodiment of the present invention includes a base 12 and a telescoping support column 14. The base 12 and the telescoping support column 14 combine to form a frame 15 which supports first and second table sections 16 and 18. In the following description, the first table section 16 may also be referred to as an upper table, and the second table section may also be referred to as a food tray. The first and second table sections 16 and 18 are mounted in vertically spaced relation proximate an upper end 17 of the support column 14. Illustratively, the first table section 16 is positioned in spaced relation above the second table section 18, thereby defining a vertical space or an open region 19 therebetween. The base 12 is generally I-shaped in plan view and is illustratively provided at its four extremities or corners with casters 20 which facilitate the convenient positioning of the overbed table 10.

WO 03/013307

PCT/US02/24619

-9-

The telescoping support column 14 illustratively extends upwardly from the base 12 at an angle of, for example, 0° to 10° generally to vertical to facilitate positioning of the overbed table 10 with respect to a conventional bed 21. More particularly, the support column 14 is configured to be positioned adjacent a conventional bed frame 22 including bed rail 23 supporting a mattress 24 (Figs. 23 and 24).

The support column 14 includes upper and lower telescoping portions 26 and 28, respectively. The upper portion 26 is configured to move in a generally vertical direction relative to the lower portion 28. Additional details of the support column 14 are provided in co-pending patent application Serial No. 09/835,002, which is assigned to the assignee of the present invention and is expressly incorporated by reference herein.

Referring further to Figs. 1, 3 and 4, a sleeve 30 is provided proximate the upper end 17 of the support column 14 and extends in a generally horizontal direction. The first table section 16 includes a rod or tube 32 having substantially the same cross-section transverse to its longitudinal axis as an interior channel 34 of the sleeve 30 (Fig. 3). The rod or tube 32 extends through the sleeve 30 and is slidably and rotatably movable about its longitudinal axis 36 within the sleeve 30, as illustrated in Figs. 3, 4, 5, and 7 to permit the first table section 16 to slide linearly away from the second table section 18 and to rotate between a generally upright vertical position and a horizontal table position.

Adjacent its upper end 17, the support column 14, as illustrated best in Figs. 1 and 3, is also provided with a beam 38 which forms a portion of the frame 15. A proximal end 40 of the beam 38 is mounted to the support column 14 and an opposite distal or remote end 42 extends from the support column 14 in a direction generally parallel to the base 12. As such, it may be appreciated that the first table section 16 is supported in a manner such that it cantilevers out from the support column 14. The remote end 42 of the beam 38 is provided with a rest 44 which limits the downward pivoting of the first table section 16 as the rod or tube 32 pivots within sleeve 30. An underside or lower surface 46 of the first table section 16 may include a bearing surface 48 which slides on the rest 44 to reduce wear on the lower surface 46 of the table section 16. A conventional latch (not shown) may be provided to releasably secure the table section 16 to the beam 38.

WO 03/013307

PCT/US02/24619

-10-

Referring now to Figs. 1-3 and 7, a storage tray or bin 49 is illustratively supported by the remote end 42 of the beam 38. The storage bin 49 includes a pair of side walls 50 and 51 and a pair of end walls 52 and 53 connected to a bottom wall 54. The end walls 52 and 53 have notches 55 formed therein to facilitate access to the storage bin 49 when the first table section 16 is positioned thereabove. A mounting tab 56 is connected to the side wall 51 and is secured to the remote end 42 of the beam 38 through a conventional fastener, such as a bolt 57 threadably received by a nut 58.

An upper surface 60 of the first table section 16 may include a plurality of recesses 61 adapted to receive and secure conventional objects that may be used by a person supported on the bed 21 or by a caregiver located adjacent to the bed 21, such as cups and plates (not shown). Additionally a bumper 62 may be secured around a peripheral edge of the first table section 16 in order to protect surfaces which may come in contact with the overbed table 10. The bumper 62 is preferably formed from a resilient material, such as an elastomer or thermoplastic.

As shown in Fig. 3, the second table section 18 includes a lower surface 63 an upper bearing 64 which is generally circular in plan view and provides a generally flat bearing surface. Intermediate the proximal end 40, adjacent the support column 14, and the distal end 42, the beam 38 is provided with a complementary lower bearing surface 66 which is also generally flat and circular. One of the second table section 18 and the beam 38 (beam 38 in the illustrated embodiment) is provided with a pivot post 68, and the other of the second table section 18 and the beam 38 (second table section 18 in the illustrated embodiment) is provided with a recess 70 for receiving the pivot post 68. The second table section 18 is releasably mounted and moves pivotally about pivot axis 72 on the pivot post 68.

On its upwardly facing surface 74 at its distal end 76 remote from the support column 14, the second table section 18 is provided with a roller bearing 78. The lower surface 46 of the first table section 16 includes a bearing track 80 for receiving the roller bearing 78 when the first table section 16 is in its lowered position resting on the rest 44. With this linkage, pivotal movement of the second table section 18 within a horizontal plane results in sliding movement of the first table section 16 along sleeve 30 in a second, parallel horizontal plane. As illustrated in Figs. 4 and 5, pivotal movement of the proximal end 82 of the second table section 18 away from

WO 03/013307

PCT/US02/24619

-11-

the support column 14 of the frame 15 in the direction of arrow 84 results in sliding movement of the first table section 16 in a generally opposite direction as represented by arrow 86 (Fig. 5). Pivotal movement of end 82 of second table section 18 toward outer support column 14 of frame 15 in the direction of arrow 88 results in sliding
5 movement of the first table section 16 in a direction generally toward the second table section 18 as represented by arrow 90.

Similarly, sliding movement of the first table section 16 away from the second table section 18 in the direction of arrow 86 results in pivotal movement of the end 82 of the second table section 18 generally away from the support column 14 in the
10 direction of arrow 84. Sliding movement of first table section 16 toward the support column 14 in the direction of arrow 90 results in pivotal movement of the end 72 of the second table section 18 toward the support column 14 and the first table section 16 in the direction of arrow 88.

Generally, it will be understood that horizontal movement in one plane of one
15 table section 16, 18 results in similar horizontal movement in an adjacent, substantially parallel plane of the other table section 16, 18. In a storage position, as illustrated in Fig. 4, the second table section 18 is positioned below the first table section 16. In the use position, as illustrated in Figs. 5 and 6, the second table section 18 is moved at least partially out from under the first table section 16.

20 The second table section 18 illustratively includes a pair of handles 92 and 94 positioned proximate opposing longitudinal side edges 96 and 97 thereof to facilitate pivoting movement of the second table section 18 about the pivot post 68. The handles 92 and 94 are configured to extend outwardly from beneath opposing side edges 98 and 99 of the first table section 16. Each handle 92 and 94 may include a
25 gripping portion 100 and 102 to be utilized by a patient in deploying the second table section 18 from the storage position (Fig. 4) to the use position (Fig. 5). The gripping portions 100 and 102 are illustratively formed from a high friction resilient material such as an elastomer.

With reference to Figs. 2-4 and 6-8, a support arm 104 is supported within the
30 open region 19 in vertically spaced relation to both the first and second table sections 16 and 18. More particularly, the arm 104 is positioned intermediate, or sandwiched between, the first and second table sections 16 and 18. The arm 104 is supported for pivoting movement within a substantially horizontal plane about a pivot axis 106 (Fig.

WO 03/013307

PCT/US02/24619

-12-

3). The lower surface 46 of the first table section 16 illustratively includes a bearing 108 which is generally circular in plan view and provides a generally flat bearing surface for the arm 104. A pivot post 110 is received within a recess 112 formed within the bearing 108. The pivot post 110 may comprise a conventional fastener
5 passing through an opening 114 formed within the arm 104 and threadably received within the recess 112. The arm 104 moves pivotally about the pivot post 110, and hence the pivot axis 106, between a storage position (Figs. 4 and 5) and a use position (Fig. 6).

The arm 104 illustratively includes a substantially U-shaped portion 116 and a
10 connecting portion 118. The U-shaped portion 116 supports a pair of handles 120 and 122 to facilitate pivoting movement of the arm 104 by a patient. The handles 120 and 122 are configured to extend outwardly from beneath the opposing side edges 98 and 99 of the first table section 16. A display screen or device 124 is supported by the U-shaped portion 116 of the arm 104 by a coupler 126.

15 With reference to Fig. 8, the coupler 126 includes a first body portion 128 supported for pivoting movement about a substantially horizontal first pivot axis 130. A first pin 132 couples the first body portion 128 to the U-shaped portion 116 of the arm 104. A second body portion 134 is supported by the first body portion 128 for pivoting movement about a second pivot axis 136 disposed substantially
20 perpendicular to the first pivot axis 130. A second pin 138 couples the second body portion 134 to the first body portion 128. In turn, the display device 124 is fixed to the second body portion 134.

The display device 124 includes first and second sides 142 and 144, with the first side 142 supporting a viewable surface 146 and configured to face toward a head
25 end 148 of the bed 21 (Fig. 23). The display device 124 illustratively comprises a conventional computer monitor wherein the viewable surface 146 comprises an electronic display 150 (Fig. 8). A conventional mirror 152 may be supported by the second side 144 of the display device 124 (Fig. 4). As may be appreciated, the user may alternatively use the electronic display 150 and the mirror 152 by simply rotating
30 the display device 124 about the second pivot axis 136 by moving the second body portion 134 around the second pin 138. In an illustrated embodiment, the display device 124 comprises a flat panel monitor and the electronic display 150 comprises a high resolution liquid crystal display. The viewable surface 146 of the display device

WO 03/013307

PCT/US02/24619

-13-

124 may be defined by other conventional screens including, but not limited to, a television screen, or a projection screen, or a conventional mirror. If the display 150 comprises a projection screen, then images may be projected from a remote location onto the viewable surface 146. More particularly, a conventional projector (not shown) may be supported by a structure (such as a ceiling) remote from the overbed table 10 and is configured to project information onto the viewable surface 146.

A processor 154 is supported by the frame 15 and most preferably is fixed proximate the upper end 17 of the support column 14. The processor 154 is in communication with the display device 124 through conventional transmission means, which may include wires or wireless transmitter and receiver (not shown). A power source in the form of a battery 156 may likewise be secured proximate an upper end 17 of the support column 14 and is in communication with the display device 124. It should be appreciated that both the processor 154 and the battery 156 may be located remote from the overbed table 10 wherein communication means are provided in order for the display device 124 to interact with the processor 154 and the battery 156, such as detailed below.

A camera 160, such as a video or digital still image camera, is illustratively supported by the display device 124. The camera 160 is in communication with the processor 154 and may have power supplied by the battery 156. In one illustrative embodiment, the camera 160 provides images to the processor 154 which are then transmitted to the electronic display 150. As such, the electronic display 150, the processor 154, and the camera 160 define an electronic mirror. In other words, the patient facing the camera 160 will see his or her image electronically generated in the electronic display 150.

A further illustrative embodiment of an overbed table 210 is shown in Figs. 9 and 10. The overbed table 210 illustratively includes a first table section 212 positioned in vertical spaced relation above a second table section 214. The first table section 212 is supported for sliding movement and the second table section 214 is supported for pivoting movement relative to the first table section 212 in the manner described above with respect to the first table section 16 and the second table section 18 of the illustrative embodiment overbed table 10.

A recess 216 extends downwardly from an upper surface 218 of the second table section 214. The display device 124 is supported by the second table section

WO 03/013307

PCT/US02/24619

-14-

214 illustratively through a hinge 220 for pivoting movement about a substantially horizontal pivot axis 222. The display device 124 is adapted to pivot about the pivot axis 222 defined by the hinge 220 between a substantially upright use position (Fig. 9) and a substantially horizontal storage position (Fig. 10). In the storage position, the display device 124 is received within the recess 216 such that the rear or second side 144 of the display device 124 is substantially flush with the upper surface 218 of the second table section 214. In the embodiment of Figs. 9 and 10, no separate support arm is required for the display device 124.

Turning now to Figs. 11 and 12, a further embodiment overbed table 310 including a frame 15 supporting a first table section 312. A storage tray 314 is supported in vertical spaced relation below the first table section 312 and is configured to move within a substantially horizontal plane in a direction generally perpendicular to a longitudinal axis 315 of the first table section 312. The display device 124 is coupled to first and second spaced apart arms 316 and 318 which provide for pivoting movement of the display device 124 from an open or use position where the display device 124 is extending upwardly out of the storage tray 314 (Fig. 11) to a closed or storage position where the display device 124 is received within the storage tray 314 below the horizontal plane defined by the first table section 312 (Fig. 12). As illustrated in Fig. 11, first ends 320 and 322 of the arms 316 and 318 are pivotally connected to longitudinally extending side walls 324 and 326 of the storage tray 314, while opposing second ends 328 and 330 of the arms 316 and 318 are pivotally connected to an upper portion of the display device 124. The first ends 320 and 322 of the arms 316 and 318 may be slidably received with channels 332 extending within the side walls 324 and 326 to facilitate folding of the display device 124 into the storage tray 314.

In operation, the display device 124 may be moved between an open position (Fig. 11) and a closed position (Fig. 12) by folding the arms 320 and 322 downwardly into the storage tray 314 such that the display device 124 is nested intermediate the side walls 324 and 326. The storage tray 314 may then be slidably moved in a direction toward the first table section 312 and into the storage position where the storage tray 314 is located in vertically spaced relation immediately below the first table section 312.

WO 03/013307

PCT/US02/24619

-15-

Referring now to Figs. 13-16, a further embodiment of the overbed table 410 of the present invention is illustrated as including a frame 15 supporting a storage unit 412. The storage unit 412 may include a plurality of shelves 414 for use by the patient or a caregiver. It should be appreciated that the shelves 414 may be enclosed
5 by doors (not shown), or replaced with sliding drawers or removable bins (not shown).

A first or upper table section 416 is slidably supported by the storage unit 412 for movement substantially parallel to the longitudinal axis 417 of the first table section 416 (Fig. 14). Moreover, the first table section 416 may include a first or
10 inner guide member 418 supported by the first table section 416, and a second or outer guide member 420 supported by the storage unit 412. As such, the table section 416 may be moved back and forth within a substantially horizontal plane in the direction of double headed arrow 422 to provide access to a storage recess 424 defined by the storage unit 412. The display device 124 is supported within the
15 storage recess 424 when in a storage position (Fig. 14). The display device 124 is supported by an arm 426 configured to move vertically relative to the table section 416. The arm 426 includes a vertical portion 428 supported by the storage unit 412 and pivotable about a substantially vertical axis 430. A horizontal portion 432 is pivotally connected to the vertical portion 428 and a coupler 434 connects the display
20 device 124 to the horizontal portion 432. The coupler 434 supports the display device 124 for a first pivoting movement about a first axis 436 and for second pivoting movement about a second axis 438 which is disposed substantially perpendicular to the first axis 436 (Fig. 16).

Referring further to Fig. 16, the coupler 434 includes a first member 440
25 rotatable about the first axis 436 and a second member 442 rotatable about the second axis 438. The arm 426 in combination with the coupler 434 provides for movement of the display device 124 into any one of a plurality of different positions as illustrated in Figs. 13-16.

As illustrated in the alternative illustrative embodiment of Figs. 17 and 18, a
30 communication device, such as a telephone 444 may be supported by the arm 426' adjacent the display device 124. Moreover, the display device 124 and the telephone 444 may be part of an overall computer system 446 coupled to a computer support 448. Fig. 17 illustrates the overbed table 410' in a use position so that the computer

WO 03/013307

PCT/US02/24619

-16-

system 446 is accessible to a patient. As such, the patient has access to email, the internet, a care plan, or other items such as computer games which are readily accessible through a computer network. The patient may also conduct business or transmit emails to caregivers asking questions. Fig. 18 illustrates the overbed table 410' in a storage position where the computer system 446 is received within the storage recess 424 below the horizontal plane of the table section 416.

Turning now to Figs. 19 and 20, a further embodiment of overbed table 510 is illustrated as including a storage unit 412 including a storage cavity or recess 424 similar to that disclosed above with respect to the overbed table 410. The display device 124 in the overbed table 510 is pivotally connected to the storage unit 412 through a hinge 512. As such, the display device 124 may be pivoted about a horizontal axis 514 between a use position where the display device 124 is positioned vertically above the table section 416 (Fig. 19) and a storage position wherein the display device 124 is received within the storage cavity 424 and below the horizontal plane of the table section 416 (Fig. 20).

Turning now to Figs. 21 and 22, a further embodiment of overbed table 610 is illustrated as again including a storage unit 412 including a storage cavity 424 similar to that detailed above with respect to the overbed table 410. The display device 124 is removably supported within the storage cavity 424. Moreover, the display device 124 may be physically removed from the storage cavity 424 and supported upon an upper surface 611 of the first table section 416 when in a use position (Figs. 21 and 22). The display device includes a collapsible stand 612 including a base 614 and at least one upright 618 connected to a rear surface 616 of the display device 124. The base 614 and the upright 618 are operably connected through a pair of pivots or hinges 620 and 622 so that the base 614 may be folded into proximity with the uprights 616 and 618 for storage within the storage cavity 424. A conventional wire or cable 624 operably connects the display device 124 to the processor 154.

Another embodiment of the present invention is illustrated in Figs. 23 and 24. The base 12 of the overbed table 710 includes a first docking connector 712 which mates with a second docking connector 714 coupled to the frame 22 of the bed 21 below the mattress 24. The first docking connector 712 coupled with second docking connector 714 may be utilized to supply electrical power to the display device 124 and to transmit information or signals thereto in a conventional manner. In a further

WO 03/013307

PCT/US02/24619

-17-

embodiment, a retractable cord 718 is utilized to supply power to the display device 124. More particularly, the retractable cord 718 is receivable within a housing 720 supported by the bed frame 22. In a further embodiment, the overbed table 710 includes a plurality of upwardly-facing solar cells 722 supported on the base 12. The solar cells 722 are utilized to power components such as the display device 124 supported on the overbed table 710. The battery 156 may be charged through ambient light by the solar cells 720 using a conventional trickle charge. For nighttime use, a night light 724 may be provided in communication with the solar cells 722. Moreover, the night light 724 is supported by the bed frame 22 and directs light downwardly toward the solar cells 722. As such, at nighttime, the night light 724 provides a source of energy to the solar cells 722 to maintain the power for the electrical components on the overbed table 710.

Additional details regarding interaction between the overbed table 10, 710 and an external computer system are provided in pending U.S. Patent Application Serial No. 09/849,580, filed May 4, 2001, U.S. Patent Application entitled "PATIENT POINT-OF-CARE COMPUTER SYSTEM" (Attorney Docket 8266-0709), filed concurrently herewith, and U.S. Provisional Application Serial No. 60/310,092, filed August 3, 2001, all of which are assigned to the assignee of the present invention.

Although the invention has been described in detail with reference to certain illustrated embodiments, variations and modifications exist within the scope and spirit of the invention as described and as defined in the following claims.

WO 03/013307

PCT/US02/24619

-18-

CLAIMS:

1. An overbed table comprising:
a frame;
a first table section coupled to said frame;
a second table section coupled to said frame in vertical spaced relation to said first table section;
a support positioned in vertical spaced relation to said first table section, said support configured to move relative to said first table section within a substantially horizontal plane; and
a display screen coupled to said support and configured to move between a substantially horizontal storage position and a substantially vertical use position.
2. The overbed table of claim 1, wherein at least one of said first table section and said second table section is configured to move in a substantially horizontal plane with respect to the other of said second table section and said first table section.
3. The overbed table of claim 2, wherein said second table section is coupled to said first table section such that movement of said second table section results in sliding movement of said first table section.
4. The overbed table of claim 1, wherein said support comprises an arm including at least one handle.
5. The overbed table of claim 4, wherein said arm includes first and second handles, and said display screen is supported intermediate said first and second handles.
6. The overbed table of claim 1, wherein said support is pivotably connected to said first table section.
7. The overbed table of claim 1, wherein said display screen is coupled to said support for pivoting movement about a substantially horizontal first axis.
8. The overbed table of claim 7, wherein said display screen is coupled to said support for pivoting movement about a second axis extending substantially perpendicular to said first axis.

WO 03/013307

PCT/US02/24619

-19-

9. The overbed table of claim 1, wherein said display screen is located intermediate said first and second table sections in said storage position and extends above said first table section in said use position.

10. The overbed table of claim 1, wherein said display screen comprises a flat panel monitor.

11. The overbed table of claim 1, wherein said display screen comprises a reflective mirror.

12. The overbed table of claim 1, further comprising a camera supported proximate said display screen.

13. The overbed table of claim 1, wherein said first table section is supported by said frame for movement between a generally vertical position and a generally horizontal position.

14. The overbed table of claim 13, wherein said second table section is releasably coupled to said first table section and said frame permits movement of said first table section between a generally vertical position and a generally horizontal position independently of said second table section.

15. The overbed table of claim 14, wherein said first table section is supported by said frame by an inner member provided on one of said frame and said first table section and an outer member provided on the other of said frame and said first table section, said inner member extending rotatably and slidably through said outer member to permit sliding movement and pivoting movement of said first table section with respect to said frame.

16. The overbed table of claim 13, further comprising a rest supported by one of said frame and said first table section, said rest configured to support said first table section in said generally horizontal position.

17. The overbed table of claim 1, wherein said frame includes a telescoping support column has an outer column portion and an inner column portion, the telescoping support column supporting said first and second table sections, and a base coupled to the telescoping support column.

18. The overbed table of claim 1, wherein said second table section is coupled to said first table section by a first pivotal coupling between said first and second table sections.

WO 03/013307

PCT/US02/24619

-20-

19. The overbed table of claim 18, wherein said first pivotal coupling includes a first bearing provided on one of said first and second table sections and a bearing race provided on said other of said first and second table sections, said first bearing engaging said bearing race to permit pivoting of said second table section about a first axis with respect to said first table section.
20. The overbed table of claim 19, wherein said second table section is coupled to said frame by a second pivotal coupling between said second table section and said frame.
21. The overbed table of claim 20, wherein said second pivotal coupling includes a trunnion provided on one of said frame and said second table section and a recess provided on the other of said frame and said second table section for receiving said trunnion to permit pivoting of said second table section about a second axis with respect to said first table section, said second axis being spaced from said first axis.
22. The overbed table of claim 21, wherein said display screen is coupled to said first table section by a third pivotal coupling connected to said first table section.
23. The overbed table of claim 1, further comprising a processor in communication with said display screen.
24. The overbed table of claim 1, further comprising a connector supported by said frame and configured to operably connect with a bed frame for placing the display screen in communication with a processor.
25. An overbed table comprising:
a frame including a vertically extending support column;
a table section supported by said frame and configured to cantilever over a patient support surface including opposing head and foot ends; and
a camera supported by said frame and directed toward the head end of the patient support surface.
26. The overbed table of claim 25, further comprising a display screen supported by said frame, said display screen including a viewable surface directed toward the head end of the patient support surface.
27. The overbed table of claim 26, wherein said camera is supported by said display screen.

WO 03/013307

PCT/US02/24619

-21-

28. The overbed table of claim 26, further comprising a support configured to move relative to said table section within a substantially horizontal plane, said display screen being coupled to said support and configured to move between a substantially horizontal storage position and a substantially vertical use position.

29. The overbed table of claim 25, further comprising a processor supported by said frame and in communication with said camera.

30. The overbed table of claim 25, further comprising a connector supported by said frame and configured to operably connect with a bed frame for placing the camera in communication with a remote processor.

31. The overbed table of claim 25, further comprising at least one solar cell supported by said frame and operably connected to said camera.

32. The overbed table of claim 31, wherein said at least one solar cell is alignable with a light source connected to the patient support surface.

33. An overbed table comprising:
a frame including a vertically extending support column;
a table section supported by said frame and configured to cantilever over a patient support surface including opposing head and foot ends; and
a display device supported by said frame and coupled to a power source, said display device including first and second sides, and a viewable surface supported by said first side and directed toward the head end of the patient support surface.

34. The overbed table of claim 33, further comprising a camera supported by said frame and directed toward the head end of the patient support.

35. The overbed table of claim 34, wherein said camera is in communication with said display device to define an electronic mirror.

36. The overbed table of claim 34, wherein said camera is supported by said display device.

37. The overbed table of claim 33, further comprising a support configured to move relative to said table section within a substantially horizontal plane, said display device being coupled to said support and configured to move between a substantially horizontal storage position and a substantially vertical use position.

38. The overbed table of claim 33, further comprising a processor supported by said frame and in communication with said display device.

WO 03/013307

PCT/US02/24619

-22-

39. The overbed table of claim 33, further comprising a connector supported by said frame and configured to operably connect with a bed frame for placing the display device in communication with a remote processor.

40. The overbed table of claim 33, further comprising at least one solar cell supported by said frame and operably connected to said display device.

41. The overbed table of claim 40, wherein said at least one solar cell is alignable with a light source connected to the patient support surface.

42. The overbed table of claim 33, further comprising a reflective mirror supported by said second side of said display device.

43. An overbed table comprising:
a table section including upper and lower surfaces, said table section being configured to cantilever over a patient support surface;
a support positioned in vertical spaced relation to said table section, at least one of said table section and said support being configured to move relative to the other of said support and said table section; and
a monitor coupled to said support and in communication with a power source.

44. The overbed table of claim 43, wherein said monitor is coupled to said support for movement between a storage position below said lower surface of said first table section and a use position extending above said upper surface of said first table section.

45. The overbed table of claim 42, wherein said support comprises an arm pivotally supported below said lower surface of said table section for pivoting movement about a substantially vertical axis.

46. The overbed table of claim 45, further comprising a coupler connecting said monitor and said arm, said coupler supporting said monitor for a first pivoting movement about a substantially horizontal axis and for a second pivoting movement about a second axis substantially perpendicular to said first axis.

47. The overbed table of claim 43, further comprising a keyboard coupled to said support.

48. The overbed table of claim 43, wherein said support comprises a tray slidably supported below said table section and defining a storage compartment, said

WO 03/013307

PCT/US02/24619

-23-

monitor supported by said tray for pivoting movement about a substantially horizontal axis.

49. The overbed table of claim 48, wherein said monitor is configured to fold into said storage compartment beneath said table section.

50. The overbed table of claim 43, wherein said monitor is supported by an arm configured to move vertically relative to said table section.

51. The overbed table of claim 50, wherein said arm includes a vertical portion, a horizontal portion pivotably connected to said vertical portion, and a coupler connecting said monitor to said horizontal portion, said coupler supporting said monitor for a first pivoting movement about a first axis and for a second pivoting movement about a second axis disposed substantially perpendicular to said first axis.

52. An overbed table comprising:
a frame;
a housing coupled to said frame and defining a storage compartment;
a table section coupled to said housing, said table section supported for movement between first and second positions, said first position substantially covering said storage compartment and said second position providing access to said storage compartment; and
a display screen coupled to a power source and removably supported within said storage compartment.

53. The overbed table of claim 52, wherein said display screen is supported by an arm including a vertical portion.

54. The overbed table of claim 53, wherein said arm includes a horizontal portion coupled to said vertical portion, and a coupler connects said display screen to said horizontal portion, said coupler supporting said display screen for a first pivoting movement about a first axis and for a second pivoting movement about a second axis disposed substantially perpendicular to said first axis.

55. The overbed table of claim 52, further comprising a collapsible stand coupled to said display screen for supporting said display screen on said table section.

56. The overbed table of claim 52, wherein said display screen comprises a flat panel monitor.

WO 03/013307

PCT/US02/24619

-24-


57. The overbed table of claim 52, further comprising a processor in communication with said display screen.

58. The overbed table of claim 52, further comprising a connector supported by said frame and configured to operably connect with a bed frame for placing the display screen in communication with a remote processor.

WO 03/013307

PCT/US02/24619


1/23

FIG-1

WO 03/013307

PCT/US02/24619

2/23


FIG - 2

WO 03/013307

PCT/US02/24619

3/23



FIG - 3



WO 03/013307

PCT/US02/24619


4/23



WO 03/013307

PCT/US02/24619

5/23




WO 03/013307

PCT/US02/24619

6/23

FIG - 7



WO 03/013307

PCT/US02/24619

7/23





FIG-8

WO 03/013307

PCT/US02/24619


8/23

FIG - 9

WO 03/013307

PCT/US02/24619


9/23

FIG-10

WO 03/013307

PCT/US02/24619

10/23




WO 03/013307

PCT/US02/24619

11/23


FIG -12



WO 03/013307

PCT/US02/24619


12/23

FIG-13

WO 03/013307

PCT/US02/24619


13/23

FIG. 14

WO 03/013307

PCT/US02/24619

14/23


FIG-15

WO 03/013307


PCT/US02/24619

15/23

FIG -16



16/23



WO 03/013307

PCT/US02/24619

17/23





FIG. 18

WO 03/013307

PCT/US02/24619

19/23


FIG - 20

WO 03/013307

PCT/US02/24619

20/23


FIG-21



WO 03/013307

PCT/US02/24619

21/23

FIG - 22

INTERNATIONAL SEARCH REPORT

Int lonal Application No

PCT/US 02/24619

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A47B23/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A47B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No. |
|------------|--|-----------------------|
| A | US 3 910 659 A (JOERNS FURNITURE COMPANY) 7 October 1975 (1975-10-07) column 1, line 62 -column 2, line 63; figures 1-4 | 1,11,17, 26,28 |
| A | EP 0 168 158 A (HAUSERMAN INC) 15 January 1986 (1986-01-15) abstract figures 1-6 | 1,43,45, 47 |
| A | US 4 848 710 A (NEWMAN) 18 July 1989 (1989-07-18) abstract, figures 3,4 | 1,33,52 |
| A | US 5 473 997 A (SOLOMON) 12 December 1995 (1995-12-12) column 3 -column 6, line 40 | 1 |

☐ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents:

A document defining the general state of the art which is not considered to be of particular relevance

E earlier document but published on or after the international filing date

L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

O document referring to an oral disclosure, use, exhibition or other means

P document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

& document member of the same patent family

Date of the actual completion of the international search

14 November 2002

Date of mailing of the international search report

21/11/2002

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Noesen, R

INTERNATIONAL SEARCH REPORT

Int lional Application No

PCT/US 02/24619

| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |
|---|---------------------|----------------------------|--------------------------|
| US 3910659 | A | 07-10-1975 | NONE |
| EP 168158 | A | 15-01-1986 | AU 4316585 A 12-12-1985 |
| | | | EP 0168158 A2 15-01-1986 |
| | | | ES 287268 U 16-11-1985 |
| | | | JP 61076105 A 18-04-1986 |
| | | | KR 9403452 B1 22-04-1994 |
| | | | NZ 212279 A 29-04-1988 |
| US 4848710 | A | 18-07-1989 | CA 1314585 A1 16-03-1993 |
| US 5473997 | A | 12-12-1995 | NONE |

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.